



Images show MWWR10 Unit

Features	MWWR5	MWWR10	Bespoke
Dimensions (length x width x height)	3000mm x 2500mm x 2000mm	3750mm x 2500mm x 2000mm	Bespoke
Sector	Marine	Marine	Marine
Coagulant Dosing	Yes	Yes	Optional
pH adjustment (Cu/Zn removal)	Yes	Yes	Optional
Number of settlement tanks	2	3	Various
Auto backwash sand filtration	Yes	Yes	Yes
Frost protection	Optional	Optional	Optional
Ingress protection (minimum)	IP54	IP54	IP54
UV sterilisation	Yes	Yes	Yes
On demand pressure pump	Optional	Optional	Optional
Auto top up	Yes	Yes	Optional
Number of washes per day (20ft boats)	Up to 5	Up to 10	Above 10
Overall Weight	7000kg	9000kg	As specified
Power	3kW/240v/single phase	3kW/240v/single phase	3kW/240v/single phase
Flow rate	20litres/minute	20litres/minute	As specified
Assumed number of pressure washers	1	1	1+

Notes: Figures are for guidance only
 All units can be located outdoor, containerised or housed in dedicated plant rooms
 Unit to be connected to mains via dedicated RCD or RCD protected circuit
 Annual pump out required by licensed waste contractor
 Rainwater (outside of operational use) must be diverted or EA permit to discharge is required

