



Images show WWR100 Unit

Features	WWR25	WWR50	WWR100	Bespoke
Dimensions (length x width x height)	3000mm x 2500mm x 2000mm	3750mm x 2500mm x 2000mm	4500mm x 2500mm x 2000mm	Bespoke
Sector	Car	Car/van	Car/van/industrial	Marine/aviation/industrial
Coagulant Dosing	Yes	Yes	Yes	Optional
Hydrogen peroxide dosing	Yes	Yes	Yes	Optional
Number of settlement tanks	2	3	4	Various
Auto backwash sand filtration	Yes	Yes	Yes	Yes
Frost protection	Optional	Optional	Optional	Optional
Ingress protection (minimum)	IP54	IP54	IP54	IP54
Auto backwash activated carbon filtration	Optional	Optional	Optional	Optional
UV sterilisation	Yes	Yes	Yes	Yes
On demand pressure pump	Optional	Optional	Optional	Optional
Auto top up	Yes	Yes	Yes	Optional
Number of washes per day	0 to 25 cars	25 to 50 cars	50 to 100 cars	100 cars +
Overall Weight	5750kg	7500kg	9500kg	As specified
Power	3kW/240v/single phase	3kW/240v/single phase	3kW/240v/single phase	3kW/240v/single phase
Flow rate	12litres/minute	24litres/minute	36litres/minute	As specified
Assumed number of pressure washers	1	2	3	3 +

Notes: Figures are for guidance only
 All units can be located outdoor, containerised or housed in dedicated plant rooms
 Unit to be connected to mains via dedicated RCD or RCD protected circuit
 Annual pump out required by licensed waste contractor

